



DRIVEGUARD™ Chuckhole Cold Patch

This is a carefully prepared blend of finely graded mineral aggregate and specially prepared asphalt and additives for adhesion and ease of use. Ready to use from the bag, it affords quick and economical repair of chuckholes in asphalt or concrete surfaces. **Chuckhole Cold Patch** sticks to asphalt and concrete without a primer even in cool, wet weather. Special packaging provides a shelf life of up to two years.

Uses

- Chuckhole repair of asphalt or concrete surfaces

Advantages

- Professional Quality - same material used by many state and local highway departments and contractors.
- All Weather – seasonally adjusted so it is as easy to use in the winter as summer.
- Easy to Use - apply directly from bag, tamp, and go.

INSTALLATION

Surface Preparation

- Sweep chuckhole clean of all dirt, dust, and debris. Remove loose pavement fragments from edges of area to be patched. Take care to keep vertical edges of chuckholes as clean as possible.

Application

- Chuckhole must be a minimum of one inch deep. Pour or shovel into chuckhole. Leave material slightly higher than desired depth to allow for compaction. Compact with flat side of shovel or tamper.

Restrictions

- Do not use over mud or clay. Material works best over a solid base.
- Do not use as a leveling compound.
- Keep bag tightly sealed when not in use.
- Do not use to make curbs, speed bumps, edges, or ramps. For filling holes only.

Cautions

- Causes eye irritation. Inhalation of vapors can be harmful to upper respiratory tract and central nervous system. Keep away from heat or flame. Wear eye and skin protection when handling. Avoid prolonged or repeated breathing of vapors, mists, or fumes. Do not take internally. Observe good hygiene and safety practices when handling this product. **KEEP OUT OF REACH OF CHILDREN!** Use only with adequate ventilation. Seal bag when not in use. **FOR EXTERIOR USE ONLY.**

PACKAGING INFORMATION

<u>Product Number</u>	<u>Size</u>	<u>Quantity</u>	<u>Weight</u>
51850	Bag	Each	50 lbs.
51860	5 Gal.	Each	73 lbs.