



•634 Route 228 • P.O. Box 599 • Mars, PA. 16046 • 724-625-3116 • FAX 724-625-1640
 •4111 Walden Ave • Lancaster, NY 14086 • 716-681-1581 • FAX 716-681-1513
 •900 W. Smith Rd. • Medina, OH 44256 • 330-723-7780 • FAX 330-723-7780
 •7301 Bessemer Avenue • Cleveland, OH 44127 • 216-341-2000 • FAX 216-341-5833



**ASPHALT COATED COTTON
 FABRIC STANDARD**

A lightweight, durable, loom woven cotton membrane thoroughly saturated with selected asphalts providing a chemical affinity for asphalt based coatings. Designed for use with hot or cold applied materials, it can be rolled out to a smooth, even layer without wrinkles. The fabric's open weave allows for complete penetration. The resulting mechanical bond between coatings, fabric and roof surface provides resilience and strength superior to that of the coating or cement alone. Available in standard or specification grade. 36" Specification grade is of the same construction, but heavier and meets the requirements of ASTM D-173, SS-C-950, Type I and AASHTO M117.

Uses

- For reinforcement of repairs, new construction or resurfacing of roofs.

Advantages

- Makes repairs with roofing cements stronger and longer lasting.
- Economical.
- Can be used with hot or cold applied products.

PACKAGING INFORMATION

Asphalt Cotton Standard Grade

<u>Product Number</u>	<u>Size</u>	<u>Quantity</u>	<u>Weight</u>
96036	36" x 150'	1/Carton	20 lbs./Carton
96024	24" x 150'	1/Carton	13 lbs./Carton
96018	18" x 150'	2/Carton	20 lbs./Carton
96012	12" x 150'	4/Carton	26 lbs./Carton
96009	9" x 150'	4/Carton	20 lbs./Carton
96006	6" x 150'	8/Carton	26 lbs./Carton
96004	4" x 150'	12/Carton	26 lbs./Carton
96003	3" x 150'	16/Carton	26 lbs./Carton

Asphalt Cotton Specification Grade

<u>Product Number</u>	<u>Size</u>	<u>Quantity</u>	<u>Weight</u>
96236	36" x 150'	1/Carton	40 lbs./Carton