



Aluminum Coating
Manufacturers, Inc.

News from

Up on the roof



7301 Bessemer Ave. • Cleve., OH 44127 • 800.556.8030 • 216.341-2000 • fax 216.341.5833

Nothing
Like It
Available
Anywhere

SAVE TIME, SAVE MONEY

Super Seal Tape

**One step permanent roof leak solution.
Even under the harshest conditions.**

Works On:

- Metal Roofs
- Tile and Shingle
- Concrete & Brick
- APP Modifies
- EPDM
- CPE
- BUR's
- SBS
- Wood
- TPO
- CSPE/HYPALON
- PVC

SUPER SEAL TAPE is a high-tech adhesive with an integrated primer in tape form originally designed for industrial use to create water-sealed, corrosion-proof pipes and stanchions under the ocean. It is a single bonded polymer with non-curing rubber, and contains no bitumen.

Only **SUPER SEAL TAPE** fixes leaks or waterproofs surfaces upon contact with the repair area, grabbing all types of surfaces. This makes **SUPER SEAL TAPE** superb for repairing, re-seaming or flashing virtually all roofs, and can be used with perfect results to install equipment curbs and skylights. Whether repairing a roof or waterproofing ductwork, no other product is as effective or easy to use.

FEATURES

- Never hardens. Won't shrink. Won't streak or ooze. Never loses its adhesive quality.
- Primer integrated right into specialized adhesive reduces pre-installation preparation and enhances the bonding process
- Requires no glues, preparation, mixing or pouring.
- Is superior to factory seams and be installed directly over old roof seams.
- Available as UV stable Super Seal, (black or white)
- Shelf life of at least 5 years

Benefits

- Reduce Inventory—One product is all you need for all roof types.
- Increase Productivity - Installs fast and easy as using a piece of tape. No Mess!
- Increase Profit - Faster installations & no wasted material or time.
- Increase Safety - No special machinery needed, no flames, gas tanks, power washers, etc.
- Work Year Round - With optional primer, can be installed to a dry surface down to -20° F.
- Flexible - Extremely flexible, even to -70° F.

Available Black/White
6" x 50' 4 rolls per case
4" x 50' 6 rolls per case

Shrink-wrapped for easy handling

PROMPT
UNBEATABLE
SERVICE

COMPETITIVE
PRICING

SHIPMENTS
IN 5 DAYS
OR LESS

HIGHEST
BUSINESS
ETHICS

55 YEARS
FAMILY
OWNED/
OPERATED

ENDURING
QUALITY





ALCM, Inc. • Roof, Foundation,
and Driveway Coatings

7301 Bessemer Ave
Cleveland, Ohio 44127
800 556 8030
216 341 2000
Fax 216 341 5833
ALCM, Inc a division
of FBC Chemical Corp

Product Data

Super Seal Tape

Black or White

One-Step,

UV stable, moisture tight

Creates air and vapor barrier

This self-sealing adhesive permanently bonds to a wide range of surfaces. Can be used on virtually any roof surface:

- EPDM
- TPO
- CSPE/HYPALON board
- SBS
- SPP Modifies
- PVC
- Galvanized Steel
- Asphalt BURs
- Coal Tar BURs
- All Metal Roofs
- Tiles
- Aluminum
- CPE
- Gypsum board
- Wood
- Polystyrene
- Fiberglass
- Brick
- Concrete
- Masonary
- PVC
- Shingle

Composition

Super Seal Tape black or White/One Step is composed of a 100% solids formulation of synthetic resins and non-curing rubber (not butyl). Designed not to harden under even the most rigorous conditions. Sag temp >200°F. Adhesive is protected (while in the roll) by a tough, easily removed polymer release liner, which prevents contamination prior to its use. Both have integrated primer in the adhesive, a patented process.

Technical Data

Color: Black, White
Standard roll size: 4", 6"
Standard case quant: 100 sq. ft. per case
Available width: Up to 48"
Peel adhesion: 20# +/-inch width
Low temperature flex: Excellent
Bacteria resistance: Excellent
Thickness: 35 +/- 2mils
Tensile PSI 4500 +/- 500: Elongation% 700+/-100
Application: To -40°F with additional primer, above 40°F with no primer.

Basic Use

Used for sealing all roof seams and leaks. **Super Seal Tape** black or White/One Step is designed to provide an air, vapor, and watertight seal on virtually all surfaces. It is also used for exterior and interior metal seam sealing. **Super Seal Tape** is ozone stable, and chemical, mold and mildew resistant. Its unique multi-polymer film backing has been specifically formulated to be resistant to UV rays, thermal expansion, impact, abrasion, and is guaranteed not to separate from the adhesive (delaminate). **Super Seal Tape** can be applied over a wide range of ambient temperatures.

Surface Preparation

Surface must be clean and dry; free of loose rust and scale, dust, talc or dirt. Oil, grease or other contaminants should be removed with a suitable solvent/cleaner.

Application

Super Seal Tape black or White/One Step is applied by removing the release liner and pressing the adhesive to the clean dry area. Rub or roll with pressure to activate bonding process.

ORDERING INFORMATION

Item # 95904 Size: 4"X50' **Color:** Black
Item # 95974 Size: 4"X50' **Color:** White

Item # 95906 Size: 6"X50' **Color:** Black
Item # 95976 Size: 4"X50' **Color:** White

WARRANTY: This product has been designed for use by persons having practical skill and experience in application. Before using, user shall determine the suitability of its product for his intended use. Since seller has no control over the specific application of this product, seller's sole warranty with respect to such product is that it is of merchantable quality control standards of ALCM, Inc. Seller make no other warranty, express or implied, and seller disclaims warranties except as set for herein. Seller shall not be liable under circumstances for consequential or incidental damages. Seller's liability for breach of warranty hereunder is limited to the purchase price of the quantity of seller's product proved to be defective.