

# High Performance 365 Days of the Year

## HP-365, The World's Best Cement

- › Formulated to use all year round- rain, sleet, snow, or sunshine
- › Sag resistant
- › Buttery consistency for easy troweling
- › Sticks under water
- › Rubberized to help prevent cracking or splitting with movement of surface

### Why Do a Messy Job Twice?

We formulate our products UP to contractor standards, not watered down to a price. Saves time, labor, and money. One application will last years longer than any conventional roof cements.



Available in 5 gallon pails, 3 gallon pails,  
1 gallon cans, and 10.5 oz plastic tubes

## Wide Variety of Uses

- › Fasten Loose Shingles
- › Seal Gutters & Downspouts
- › Chimneys
- › Set or Fix Flashings
- › Copings
- › Skylights
- › Roof Fans
- › Vents
- › Concrete
- › Metal
- › Masonry
- › Asphalt Built Up Roofs



### Preparation

Remove dirt, dust, and debris with stiff brush, forced air, or pressure washer. Remove rust with a wire brush. If using on metal roof, securely fasten any loose panels before using cement.



### Application

Coating must be thoroughly stirred prior to and occasionally during use.

Tools for the job:

- Trowel
- Putty Knife
- Rubber Gloves



### Approximate Coverage Rate

8 gallons per 100 square feet.  
(Will vary depending on porosity and smoothness of the surface)

**FOR EXTERIOR USE ONLY**



# HP-365 SBS Rubberized Flashing Cement



---

## Specifications

**Percent Solids by Weight = 70%**  
**Percent Solids by Weight = 63%**  
**Weight per Gallon = 8.41 lbs**  
**Flash Point-minimum = 105°F (Seta C.C.)**  
**P.H. = n/a**  
**Viscosity at 77° F = 450,000 cps**  
**Long-Term Service Temperature = 60°F + 160°F**

**U.V. Resistance = Excellent**  
**VOC = < 300 g/l**

**Water Resistance:**  
Intermittent Exposure = Excellent  
Ponded = Good

---

## Products

PRODUCT #	SIZE	QTY	WEIGHT
<b>A47605</b>	<b>5 gal.</b>	<b>Each</b>	<b>45 lbs.</b>
<b>A47603</b>	<b>3 gal.</b>	<b>Each</b>	<b>28 lbs.</b>
<b>A47607</b>	<b>10.5 oz tube</b>	<b>Case of 12</b>	<b>14 lbs.</b>

---

### Cautions

This product is combustible. Keep away from heat, sparks, and open flame. Avoid breathing of vapors. Avoid repeated or prolonged contact with skin. If swallowed, do not induce vomiting. Contact a physician immediately. Keep container closed when not in use. Since empty containers contain product residue (vapors or liquid), all labeled hazardous precautions must be observed. Do not reuse empty pail. Dispose of empty containers in accordance with all applicable local, state, and federal regulations. Keep Away from Children.

Product label and Material Safety Data Sheet contain further information on the safe use of this product and precautions for the safe disposal of the container. They should be read and understood prior to use.



A Division of FBC Chemical